

NORTH CAROLINA

Department of Transportation




















2018 DCE Mtg. - Structures

Cameron Cochran & Aaron Earwood

October 24, 2018

PPC Overlay Projects by Division



Polyester Polymer Concrete

- New to almost every office
- Covered in Winter Structures Training
- Reoccurring issues
 - Manufacturer's Rep Onsite?

Scarification of Gutterline



Expansion Joints



Shotblasting



After shotblasting, traffic not allowed prior to overlay.

Grooving vs Tining



PPC with Stringline




Structure Surveying




Structure Surveying

TYPICAL BRIDGE-TANGENT SURVEY LAYOUT



- BL Survey Control
 Points
 Cap and Rebar Set
 by NCDOT.
- Bridge Reference Points-Tacked hubs with guard stakes and offsets along reference lines for each work point.
- Survey Reference Points-Tacked hubs with guard stakes and offsets along reference lines for each work point. Acceptable to use Mag Nails when work points or survey reference is on paved surfaces.

Bridges should not be layed out using radial stakeout unless prior approval has been obtained.



Structure Completion



Structure Completion

- Send emails of notices to <u>SIA@ncdot.gov</u>
- Include in the email:
 - Hyperlink to the form
 - Contract number
- Don't forget to Accept the document
- Upload as builts
- Attach shop and working drawings to the email

Bridge Deck Rideability

- Rainhart Profilograph Outdated
 - Zero Inch Blanking Band
 - Almost guarantees failure and need to diamond grind
 - Can use an Inertial Profiler to simulate Rainhart

Bridge Deck Rideability

- International Roughness Index (IRI)
 - Draft Provision
 - Divisions can request to use in lieu of Rainhart
 - Goal to replace Rainhart in Special Provisions

- Corrective Diamond Grinding
 - Pay for under Grooving Pay Item